


# HSM Shredder Baler Combinations

## Product Overview



# We generally ensure one thing: quality right down to the last detail.



## Reliable: the functioning

- Material intake via practical loading table and conveyor belt
- Optimised transfer technology prevents the material from passing the cutting device without being shredded
- Closed, dust-free material transfer from the document shredder directly into the downstream baling press
- Easy and quick handling by means of automatic control
- Shredding and pressing conducted simultaneously



## Intelligent: the control

- Integrated controller for both document shredder and baling press
- Document shredder with keypad for continuous operation and reverse as well as automatic reverse in the event of a paper jam
- Modern controller with multi-language display and convenient menu guidance
- Automatic control of the compression process
- Display to indicate „bale ready“



## Sturdy: the technology

- Extremely sturdy cutting device with specially hardened, solid steel cutting rollers
- Insensitive to smaller metal parts
- Also shreds chip cards, CDs, disks and other similar material
- Cutting device driven by powerful motor
- Sturdy gear motor with chain drive for maximum throughput capacity
- Torsion-resistant press ram guidance prevents overcharging



## Efficient: the result

- Highly compacted shredder material in boxes / plastic bags or as bale
- Highest throughput capacities at low power consumption
- Mobile due to castors



## Special features:

- Integrated, manual oiler for cutting unit for all particle cut versions
- Extension of loading table to the right or left available upon request for SP 4040 V model

Combination has great advantages. Together with all detail solutions, each user gets the maximum benefits. Durability, economic efficiency, operator-friendly, high pressing power and highest throughput capacities – these are the typical plus points that each HSM shredder baler combination can be credited for.

## HSM SP 4040 V

### A neat machine all round

The HSM SP 4040 V is the starter model in the shredder baler combination sector and the top model in terms of efficiency and space-saving set-up surface!

- Especially compact and space-saving vertical design
- Also shreds computer lists, stacks of documents or daily waste from numerous waste-paper baskets
- Extension of loading table to the right or left upon request



**Cutting capacity:** up to 130 sheets per cycle  
**Pressing power:** 44 kN  
**Hourly output:** up to 8 bales / boxes à 25 - 35 kg



## HSM SP 4940 V

### High output in a compact space

With even more power than the HSM SP 4040 V, the HSM SP 4940 V has an impressive cutting capacity per cycle.

- Optimum efficiency with HSM technology
- Complete disposal unit with minimum space requirements
- Specially for continuous operation in large departments and archives



**Cutting capacity:** up to 320 sheets per cycle  
**Pressing power:** 44 kN  
**Hourly output:** up to 10 bales / boxes à 25 - 35 kg



- Automatic control of the pressing process by means of border light sensors
- Compression of the shredder material directly in boxes or plastic bags
- No strapping necessary for easy and time-saving handling
- Easy removal from boxes or bags with removal trolley
- Standard equipment: 5 boxes, 5 plastic bags, bag holder, 1 removal trolley

# HSM SP 4980 / HSM SP 5080

## HSM SP 4980

### The compact semi-automatic model

In terms of economic efficiency the HSM SP 4980 is very difficult to beat. It combines power and convenient operation in one compact power-pack like no other device.

- Compact, space-saving design
- Efficient document disposal unit for professional use
- Specially for continuous operation in large departments and archives

**Cutting capacity:** up to 440 sheets per cycle

**Pressing power:** 80 kN

**Hourly output:** up to 9 bales à 60 - 80 kg



## HSM SP 5080

### The inexpensive alternative in the premium class

The HSM SP 5080 is a compact, high performance unit. It produces very dense bales, cleanly packaged in a plastic bag, ready for transport.

- Folders and their contents, bound computer lists or stacks of paper as thick as telephone directories are processed with ease
- The size of the bales allows two bales to fit on a Euro pallet
- Ideal as central document shredding point

**Cutting capacity:** up to 650 sheets per cycle

**Pressing power:** 80 kN

**Hourly output:** up to 10 bales à 60 - 80 kg



- Automatic photoelectric control of the pressing process
- Shredder material compressed directly in the collecting bag without strapping
- No strapping necessary for easy and time-saving handling
- Service flap above the conveyor belt for service and cleaning work
- User-friendly hydraulic counterplate
- Standard equipment: 5 plastic bags



## HSM SP 4988

### The semi-automatic professional solution

The HSM SP 4988 is the disposal unit which offers excellent price-/ performance ratio. The powerful shredder and semi-automatic press with strapping form a highly effective team.

- Low-noise, energy-saving technology
- Efficient material shearing system for protruding material at the press ram
- Dust scrapers on the inside of the conveyor belt increase both service life and reliability



**Cutting capacity:** up to 440 sheets per cycle  
**Pressing power:** 85 kN  
**Hourly output:** up to 7 bales à 70 - 95 kg



## HSM SP 5088

### Well-equipped for the long run

With its powerful 9.2 kW motor, the HSM SP 5088 combines high power with the advantages of a channel baling press.

- Optimal loading for maximum throughput capacities in continuous operation
- Bulky cardboard packaging and other material which does not have to be shredded can be filled in directly via the large loading aperture
- Top model as central disposal system for administration offices, banks and authorities etc.

**Cutting capacity:** up to 650 sheets per cycle  
**Pressing power:** 85 kN  
**Hourly output:** up to 9 bales à 70 - 95 kg



- Channel baling press with loading aperture / inspection flap for direct compression of cardboard or packaging material etc.
- Automatic press channel adjustment for constant pressing power
- Variable bale length setting
- Manual, 3-fold strapping with continuous polyester tape
- Equipped as standard with polythene bag attachment, basic equipment: 5 plastic bags

# HSM SP 50100

## HSM SP 50100

### The top model for highest demands

The powerful shredder, which is combined with a fully-automatic baler, ensures maximum throughput capacities. The HSM SP 50100 is the model for highest demands in continuous operation.

- Material infeed optionally via inclined conveyor belt and pre-shredder
- Retaining claws in the press channel and automatic return stroke for perfect bale results
- Professional disposal system for the waste disposal industry with maximum throughput capacity at low power consumption



**Cutting capacity:** up to 650 sheets per cycle  
**Pressing power:** 110 kN  
**Hourly output:** up to 12 bales à 60 - 120 kg

- Baler with loading aperture / inspection flap for direct compression of cardboard or packaging material etc.
- Efficient material shearing system for protruding material at the press ram
- Automatic press channel adjustment for constant pressing power
- Variable bale length setting
- Fully-automatic 3-fold strapping with patented coiled wire
- Equipped as standard with polythene bag attachment, basic equipment: 5 plastic bags

Cutting type Cutting size in mm		Security level DIN 32757-1	Cutting capacity per cycle in sheets, DIN A4, 70 g/m <sup>2</sup>	Cutting capacity per cycle in sheets, DIN A4, 80 g/m <sup>2</sup>	Throughput capacity in kg/h, DIN A4, 70 g/m <sup>2</sup>	Cutting speed in mm/s	Working width in mm	Motor in kW (document shredder / baling press)	Voltage / frequency in V/Hz	Pressing power in kW	Max. bale size in mm (W x H x L)	Bale weight in kg (depending on material)	Hourly output in bales/boxes (depending on material)	Dimensions of the machine in mm (W x D x H)	Machine weight in kg
<b>HSM SP 4040 V</b>															
Strips	5.8	2	130	104	370	210	428	4.0 / 2.2	3 x 400 / 50	44	600 x 500 x 400	25 - 35	6 - 8	1090 x 2030 x 1970	737
Particle	5.8 x 5.0	3	120	96	370	230	428	4.0 / 2.2	3 x 400 / 50	44	600 x 500 x 400	25 - 35	6 - 8	1090 x 2030 x 1970	737
<b>HSM SP 4940 V</b>															
Strips	5.8	2	160 - 180	120 - 140	400	235	500	6.0 / 2.2	3 x 400 / 50	44	600 x 500 x 400	25 - 35	6 - 10	1160 x 2330 x 1970	1030
Particle	7.5x40-80	2	300 - 320	240 - 260	750	250	500	6.0 / 2.2	3 x 400 / 50	44	600 x 500 x 400	25 - 35	8 - 10	1160 x 2330 x 1970	1030
Particle	4.5x40-70	3	200 - 220	160 - 180	550	250	500	6.0 / 2.2	3 x 400 / 50	44	600 x 500 x 400	25 - 35	6 - 10	1160 x 2330 x 1970	1030
<b>HSM SP 4980</b>															
Strips	10.5	1	230 - 250	180 - 200	500	235	500	6.0 / 4.0	3 x 400 / 50	80	570 x 490 x 800	60 - 80	6 - 7	1160 x 2750 x 1350	1265
Strips	5.8	2	160 - 180	120 - 140	400	235	500	6.0 / 4.0	3 x 400 / 50	80	570 x 490 x 800	60 - 80	4 - 6	1160 x 2750 x 1350	1265
Particle	10.5x40-76	2	420 - 440	330 - 350	600	250	500	6.0 / 4.0	3 x 400 / 50	80	570 x 490 x 800	60 - 80	7 - 9	1160 x 2750 x 1350	1265
Particle	7.5x40-80	2	300 - 320	240 - 260	500	250	500	6.0 / 4.0	3 x 400 / 50	80	570 x 490 x 800	60 - 80	6 - 8	1160 x 2750 x 1350	1265
Particle	4.5x40-70	3	200 - 220	160 - 180	440	250	500	6.0 / 4.0	3 x 400 / 50	80	570 x 490 x 800	60 - 80	6 - 7	1160 x 2750 x 1350	1265
<b>HSM SP 5080</b>															
Particle	10.5x40-76	2	600 - 650	510 - 550	700	210	500	9.2 / 4.0	3 x 400 / 50	80	570 x 490 x 800	60 - 80	8 - 10	1155 x 2650 x 1410	1330
Particle	7.5x40-80	2	500 - 550	425 - 470	600	210	500	9.2 / 4.0	3 x 400 / 50	80	570 x 490 x 800	60 - 80	7 - 9	1155 x 2650 x 1410	1330
Particle	6x40-53	3	400 - 450	340 - 380	500	210	500	9.2 / 4.0	3 x 400 / 50	80	570 x 490 x 800	60 - 80	6 - 8	1155 x 2650 x 1410	1330
<b>HSM SP 4988</b>															
Strips	10.5	1	230 - 250	180 - 200	450	235	500	6.0 / 4.0	3 x 400 / 50	85	500 x 500 x max. 950	20 - 95	4 - 5	1280 x 3530 x 1350	1537
Strips	5.8	2	160 - 180	120 - 140	350	235	500	6.0 / 4.0	3 x 400 / 50	85	500 x 500 x max. 950	20 - 95	3 - 4	1280 x 3530 x 1350	1537
Particle	10.5x40-76	2	420 - 440	330 - 350	550	250	500	6.0 / 4.0	3 x 400 / 50	85	500 x 500 x max. 950	20 - 95	6 - 7	1280 x 3530 x 1350	1537
Particle	7.5x40-80	2	300 - 320	240 - 260	440	250	500	6.0 / 4.0	3 x 400 / 50	85	500 x 500 x max. 950	20 - 95	5 - 6	1280 x 3530 x 1350	1537
Particle	4.5x40-70	3	200 - 220	160 - 180	400	250	500	6.0 / 4.0	3 x 400 / 50	85	500 x 500 x max. 950	20 - 95	4 - 5	1280 x 3530 x 1350	1537
<b>HSM SP 5088</b>															
Particle	10.5x40-76	2	600 - 650	510 - 550	730	210	500	9.2 / 4.0	3 x 400 / 50	85	500 x 500 x max. 950	20 - 95	8 - 9	1240 x 3430 x 1410	1600
Particle	7.5x40-80	2	500 - 550	425 - 470	630	210	500	9.2 / 4.0	3 x 400 / 50	85	500 x 500 x max. 950	20 - 95	7 - 8	1240 x 3430 x 1410	1600
Particle	6x40-53	3	400 - 450	340 - 380	550	210	500	9.2 / 4.0	3 x 400 / 50	85	500 x 500 x max. 950	20 - 95	6 - 7	1240 x 3430 x 1410	1600
<b>HSM SP 50100</b>															
Particle	10.5x40-76	2	600 - 650	510 - 550	950	210	500	9.2 / 7.5	3 x 400 / 50	110	570 x 490 x max. 1200	60 - 120	9 - 12	2240 x 4360 x 1770	2526
Particle	7.5x40-80	2	500 - 550	425 - 470	790	210	500	9.2 / 7.5	3 x 400 / 50	110	570 x 490 x max. 1200	60 - 120	8 - 11	2240 x 4360 x 1770	2526
Particle	6x40-53	3	400 - 450	340 - 380	640	210	500	9.2 / 7.5	3 x 400 / 50	110	570 x 490 x max. 1200	60 - 120	8 - 9	2240 x 4360 x 1770	2526

**Detailed technical data and dimensions:**

Cutting size in mm	Dimension of the strips or particles of the shredded material (depending on the paper quality).
Security levels	In accordance with DIN 32757-1.
Cutting capacity* per cycle	The max. number of sheets (DIN A 4, 70g/m <sup>2</sup> or 80 g/m <sup>2</sup> ), fed lengthwise, with cold motor and lubricated cutting unit, which can be cut in one cycle.
Throughput capacity in kg/h	Max. volume that can be theoretically shredded in one hour.
Cutting speed in mm/s	This is calculated on the basis of the external diameter and speed of the cutting rollers in idle operation.
Working width in mm	Maximum effective width of the feed opening.
Motor in kW	Power consumption of the document shredder motor at maximum cutting capacity* (see above)
	Power consumption of the baler motor in normal operation.
Voltage / frequency in V/Hz	Three-phase/alternating current power supply.
Pressing power in kN	Piston cylinder surface multiplied by the maximum hydraulic pressure (theoretical value).
Max. bale size W x H x L in mm	The length/height of the bales varies according to the expansion force of the compressed material.
Bale weight in kg	The bale weight varies depending on the type, moisture and condition of the compressed material and the bale length/height.
Hourly output in bales/boxes	The hourly output depends on the type and quantity of the material to be pressed and on the number of persons loading the machine.
Dimensions of the machine	External dimensions of the machine when ready for operation.
W x D x H in mm	
Machine weight in kg	Net weight of machine without packaging, loaded material or options.



## Germany:

HSM Pressen GmbH + Co. KG  
Bahnhofstrasse 115  
88682 Salem

Sales:  
Werk Frickingen  
Austrasse 1  
88699 Frickingen

Tel. +49 (0) 75 53 / 822-0  
Fax +49 (0) 75 53 / 822-160  
info@hsm-online.de

## International:

HSM Pressen GmbH + Co. KG  
Adresse salle d'exposition:  
Paris Nord II  
33 rue des Chardonnerets  
95971 ROISSY  
Adresse postale:  
1 rue de la Haye  
Le Dôme - BP 12910  
95731 ROISSY CDG CEDEX  
Tel. N°Azur 0810.12.26.33  
PRIX APPEL LOCAL  
Fax: N°Indigo 0820.20.84.80  
0,118 EURO TTC / MN  
HSM.France@hsm-online.de

HSM Pressen GmbH + Co. KG  
Oficina Barcelona  
Plaça dels Nostres Avis, 3  
08450 Llinars del Vallès  
BARCELONA  
Tel. +34 93.84.10.760  
Fax +34 93.84.10.631  
HSM.Spain@hsm-online.de

HSM Verkoop Nederland  
Tel. 0800 0203740  
Fax 0800 0203739  
HSM.Benelux@hsm-online.de

HSM Verkoop België + Luxembourg  
Tel. +49 (0) 75 53 / 822-354/271  
Fax +49 (0) 75 53 / 822-260  
HSM.Benelux@hsm-online.de

HSM Sales Austria  
Tel. +49 (0) 75 53 / 822-222  
Fax +49 (0) 75 53 / 822-272  
HSM.Austria@hsm-online.de

HSM of America LLC  
1075 Andrew Drive, Suite C  
West Chester  
PA 19380  
Tel.: (610) 918-4894  
(800) 613-2110  
Fax: (610) 918-4899  
customerservice@hsmofamerica.com  
info@hsmofamerica.com  
www.hsmofamerica.com

HSM (UK) Ltd.  
14 Attwood Road / Zone 1  
Burntwood Business Park  
Burntwood  
Staffordshire  
WS7 3GJ  
Tel. +44 (0) 1543.272.480  
Fax +44 (0) 1543.272.080  
info@hsmuk.co.uk  
www.hsmuk.co.uk

[www.hsm-online.de](http://www.hsm-online.de)

Your HSM partner

**HSM**®