

HSM V-Press 860 L
The vertical baling press
for easy bale transport
without the need for pallets



HSM V-Press 860 L

The innovation in easy bale handling and transport by hand pallet truck / fork lift truck

With a pressing power of 532 kN and low-noise and energy-saving technology, the HSM vertical baling press V-Press 860 is the most economical and ecological solution for your waste disposal. The HSM V-Press 860 L produces bales with a recess for easy transport without pallets.

- Compresses used packaging material such as cardboard and foil
- Flexible and fixed retaining claws optimise material compression and reduce the number of filling processes
- User-friendly membrane keypad with text display, which shows the current status of the machine
- High level of operational safety due to automatic startup when the doors are closed and the compressing procedure stops automatically when the doors are opened.
- Solid press ram and extremely stable press ram guide
- Integrated HSM TCS (TorsionControlSystem) prevents one-sided overloading during the pressing procedure
- Standard strapping with wire, optional tape strapping
- Special profiles in the bale ejection door, in the filling hatch and in the press ram form recesses in the bales.
- No need for pallets. The bales can be easily moved with a pallet truck or fork lift truck.
- Configuration:
Double doors with hydraulic door lock



Volume reduction of packaging material by up to 95%



Special profiles form a recess in the bales



Convenient bale discharge device



Compact bales can be transported without pallets

Model	HSM V-Press 860 L
Motor in kW	7.5
Pressing power in kN	532
Voltage / frequency	3 x 400 V / 50 Hz
Loading aperture W x H in mm	1195 x 650
Bale weight in kg (depending on material)	Up to 460
Maximum bale size L x W x H (mm)	1200 x 780 x max. 1200
Hourly output in bales	1 - 2
Cycle time in idle operation (theor.) in seconds	46
Volume throughput in idle operation (theor.) in m ³ /h	57
Press chamber size W x D x H in mm	1195 x 780 x 1640
Dimensions of machine W x D x H in mm	1785 x 1035 x 2990
Weight in kg	approx. 1920
Strapping	4-fold with wire / optional polyester strapping

All technical data and dimensions are approximate values only. Technical and design changes reserved.